



Product Specification and Technical Data

PRODUCT: BG SS 2000 Grease

PART NO.: 608



NLGI DATA: NLGI Grade: 2 NLGI Approved: GC-LB Texture: Smooth
Color: Green Thickener Type: Polyurea

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	Worked Penetration, 60 Strokes	D 217265-295
	Water Washout, % loss	D 12642.0
	Dropping Point	D 2265	>260°C (>500°F)
	Oxidation Stability @ 99°C (210°F), 100 hours	D 942	5 max
	Copper Corrosion, Rating	D 4048	1b
	Oil Separation, % loss	D 17420.3
	Four Ball EP, Weld Point, min	D 2596	400
	Load Wear Index, Kgf	D 259650
	Four Ball Wear, Scar Dia. mm	D 22660.5
	Rust Prevention	D 1743	Pass
	Timken, OK Load, lbs. min	D 250960
	Base Fluid Properties:		
	Viscosity, cSt @ 100°C (212°F).	D 44511.6
	Viscosity, cSt @ 40°C (104°F)	D 445129
	Viscosity Index (min.)	D 227071
	Low Temperature Torque, -40°C, NM	D 46936.6

DESCRIPTION: BG SS 2000 is a technologically advanced multi-purpose lubricating grease. It performs exceptionally well in automotive, marine and industrial environments. BG SS 2000 can be applied with complete confidence in hot or cold temperatures, under wet or dry conditions, with light or heavy loads.

BG SS 2000 is virtually insensitive to water and protects against rust. Its versatility provides excellent seal compatibility with many materials and permits mixture with other soap-based greases. High dropping point in excess of 500°F (260°C) and outstanding low temperature mobility makes BG SS 2000 the grease for all seasons.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.